



Model: WD WD6000BKHG

S/N: WXL1E61LZDC8

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **WD WD6000BKHG**

Serial: **WXL1E61LZDC8**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/16 17:21:51**

End time: **2025/02/16 22:01:41**

Duration: **04:39:50**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **107 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD6000BKHG

S/N: WXL1E61LZDC8



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD
product: WD6000BKHG
revision: D1V8
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50014ee300102d98
serial number: WXL1E61LZDC8
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 16 22:01:43 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C
drive trip temperature: 64 C

accumulated power on time, hours:minutes 110898:57
manufactured in week of year 2010
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 8
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 8
elements in grown defect list: 9

error counter log:

	errors corrected by	total errors	correction algorithm	gigabytes processed	total uncorrected errors		
	ecc	rereads/rewrites		[10 ⁹ bytes]			
read:	45134003	59777	58491	45193780	61172	1.665	0
write:	214347	1813165	0	2027512	1813165	1.038	0
verify:	446639	708	729	447347	712	0.229	0

non-medium error count: 2089500

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	32	3	-	[- - -]
# 2	background short	completed	32	1	-	[- - -]

long (extended) self-test duration: 8460 seconds [141.0 minutes]