



Model: WD WD6000BKHG

S/N: WXF1E61KEJ50



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **WD WD6000BKHG**

Serial: **WXF1E61KEJ50**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/16 17:18:43**

End time: **2025/02/16 22:16:12**

Duration: **04:57:29**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **100 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: WD WD6000BKHG

S/N: WXF1E61KEJ50



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD
product: WD6000BKHG
revision: D1V8
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50014ee3aabad7ec
serial number: WXF1E61KEJ50
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 16 22:16:13 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 44 C
drive trip temperature: 64 C

accumulated power on time, hours:minutes 110898:57
manufactured in week of year 2010
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 8
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 8
elements in grown defect list: 5

error counter log:

	errors corrected by	total	correction	gigabytes	total
	ecc	errors	algorithm	processed	uncorrected
	fast delayed	rewrites	corrected	invocations	errors
read:	33099814 34052	35896	33133866	36719	4.081 0
write:	205137 1783096	0	1988233	1783096	1.018 0
verify:	451663 1643	2306	453306	1736	0.232 0

non-medium error count: 2368307

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	32	3	-	[- - -]
# 2	background short	completed	32	1	-	[- - -]

long (extended) self-test duration: 8460 seconds [141.0 minutes]