



Model: WD WD6000BKHG

S/N: WXF1E61KEH23



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: Not Applicable (BN)

Business Address: Not Applicable (BA)

Contact Name: Not Applicable (BCN)

Contact Phone: Not Applicable (BCP)

Customer Details

Name: Not Applicable (CN)

Address: Not Applicable (CA)

Contact Name: Not Applicable (CCN)

Contact Phone: Not Applicable (CP)

Disk Information

Make/Model: WD WD6000BKHG

Serial: WXF1E61KEH23

Size(Apparent): 600 GB, 600127266816 bytes

Bus: SAS

Size(Real): 600 GB, 600127266816 bytes

Disk Erasure Details

Start time: 2025/02/16 17:18:16

End time: 2025/02/16 22:38:06

Duration: 05:19:50

Status: **ERASED** See Warning !

Method: PRNG Stream

PRNG algorithm: XORshiro256

Final Pass(Zeros/Ones/None): Zeros

Verify Pass(Last/All/None): Verify Last

*Bytes Erased: 600127266816, (100.00%)

Rounds(completed/requested): 1/1

HPA/DCO: Unknown

HPA/DCO Size: Unknown

Errors(pass/sync/verify): 0/0/0

Throughput: 93 MB/sec

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: Not Applicable (OTN)



Model: WD WD6000BKHG

S/N: WXF1E61KEH23



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD
product: WD6000BKHG
revision: D1V8
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50014ee3aabad89c
serial number: WXF1E61KEH23
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 16 22:38:08 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 46 C
drive trip temperature: 64 C

accumulated power on time, hours:minutes 110899:33
manufactured in week of year 2010
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 8
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 8
elements in grown defect list: 78

error counter log:

	errors corrected by	total	correction	gigabytes	total
	ecc	errors	algorithm	processed	uncorrected
	fast delayed	rereads/ rewrites	invocations	[10^9 bytes]	errors
read:	98941214 688557	1198004	99629771 692251	3.768	0
write:	680695 2140886	0	2821581 2140899	1.445	9
verify:	1039924 199925	345146	1239849 200403	0.635	91

non-medium error count: 1275068

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	32	3	-	[- - -]
# 2	background short	completed	32	1	-	[- - -]

long (extended) self-test duration: 8460 seconds [141.0 minutes]