



Model: SEAGATE ST32000645SS

S/N: 9XH04MXX

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST32000645SS**

Serial: **9XH04MXX**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

Disk Erasure Details

Start time: **2025/02/16 10:38:13**

End time: **2025/02/17 01:53:48**

Duration: **15:15:35**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **109 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST32000645SS

S/N: 9XH04MXX

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST32000645SS
revision: RS16
compliance: SPC-4
user capacity: 2,000,398,934,016 bytes [2.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x5000c5004249ee07
serial number: 9XH04MXX
device type: disk
transport protocol: SAS (SPL-3)
local time is: Mon Feb 17 01:53:50 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 26813:13
manufactured in week 30 of year 2012
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 2
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 84145
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 682843635
blocks received from initiator = 2326496990
blocks read from cache and sent to initiator = 3983237344
number of read and write commands whose size <= segment size = 9588102
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 26813.22
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by			total	correction		gigabytes	total
	ecc			errors	algorithm		processed	uncorrected
	fast	delayed	rereads/ rewrites	corrected	invocations		[10^9 bytes]	errors
read:	3132359317	0	0	3132359317	0	0	16824.803	0
write:	0	0	0	0	0	0	5600.786	0
verify:	2845404201	0	0	2845404201	0	0	287101.692	0

non-medium error count: 11769

no self-tests have been logged