



Model: WD WD6002BKTG

S/N: WXE1E24FNL74



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: Not Applicable (BN)

Business Address: Not Applicable (BA)

Contact Name: Not Applicable (BCN)

Contact Phone: Not Applicable (BCP)

Customer Details

Name: Not Applicable (CN)

Address: Not Applicable (CA)

Contact Name: Not Applicable (CCN)

Contact Phone: Not Applicable (CP)

Disk Information

Make/Model: WD WD6002BKTG

Serial: WXE1E24FNL74

Size(Apparent): 600 GB, 600127266816 bytes

Bus: SAS

Size(Real): 600 GB, 600127266816 bytes

Disk Erasure Details

Start time: 2025/02/17 04:45:11

End time: 2025/02/17 04:47:06

Duration: 00:01:55

Status: **FAILED**

Method: PRNG Stream

PRNG algorithm: XORshiro256

Final Pass(Zeros/Ones/None): Zeros

Verify Pass(Last/All/None): Verify Last

*Bytes Erased: 409600000, (0.06%)

Rounds(completed/requested): 0/1

HPA/DCO: Unknown

HPA/DCO Size: Unknown

Errors(pass/sync/verify): 1/1/0

Throughput: 3561 KB/sec

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: Not Applicable (OTN)



Model: WD WD6002BKTG

S/N: WXE1E24FNL74



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: WD
product: WD6002BKTG
revision: D1P3
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50014ee755956b70
serial number: WXE1E24FNL74
device type: disk
transport protocol: SAS (SPL-3)
local time is: Mon Feb 17 04:47:09 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 13 C
drive trip temperature: 50 C

accumulated power on time, hours:minutes 90174:07
manufactured in week 21 of year 2014
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 25
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 1459
elements in grown defect list: 17

error counter log:

	errors corrected by	total errors	correction algorithm	gigabytes processed	total uncorrected errors
	ecc	rereads/rewrites	corrected	invocations	
	fast delayed				
read:	2601699733 153938	1814391	2601853671	153950	201505.776
write:	1886480884 5	39983	1886480889	5	224883.220
verify:	13808226 1645066	68678645	15453292	1648200	20490.608

non-medium error count: 57619

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	48	6	-	[- - -]
# 2	reserved(7)	completed	32	6	-	[- - -]
# 3	background short	completed	48	4	-	[- - -]

long (extended) self-test duration: 4144 seconds [69.1 minutes]