



Model: SEAGATE ST9146853SS

S/N: 6XM26E78

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST9146853SS**

Serial: **6XM26E78**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/17 04:44:19**

End time: **2025/02/17 05:31:21**

Duration: **00:47:02**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **156 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9146853SS
S/N: 6XM26E78



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9146853SS
revision: YS09
compliance: SPC-4
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5005f30395f
serial number: 6XM26E78
device type: disk
transport protocol: SAS (SPL-3)
local time is: Mon Feb 17 05:31:23 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 67163:22
manufactured in week 04 of year 2013
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 26
elements in grown defect list: 434

vendor (seagate cache) information

blocks sent to initiator = 2266500706
blocks received from initiator = 1378558727
blocks read from cache and sent to initiator = 46817251
number of read and write commands whose size <= segment size = 955960059
number of read and write commands whose size > segment size = 42

vendor (seagate/hitachi) factory information

number of hours powered up = 67163.37
number of minutes until next internal smart test = 12

error counter log:

	errors corrected by	total errors	correction algorithm	gigabytes processed	total uncorrected errors		
	ecc	rereads/rewrites		[10^9 bytes]			
	fast delayed		corrected	invocations			
read:	2706192766	5	0	2706192771	5	819.820	0
write:	0	0	0	0	1	133243.466	0
verify:	3237210995	43	0	3237211038	43	74029.383	0

non-medium error count: 6

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	32	2	-	[- - -]
# 2	background long	completed	32	1	-	[- - -]
# 3	background short	completed	32	1	-	[- - -]

long (extended) self-test duration: 1099 seconds [18.3 minutes]