



Model: SEAGATE ST9146853SS  
S/N: 6XM30AEG



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST9146853SS**

Serial: **6XM30AEG**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

## Disk Erasure Details

Start time: **2025/02/17 04:44:40**

End time: **2025/02/17 05:32:23**

Duration: **00:47:43**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **153 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9146853SS  
S/N: 6XM30AEG



# Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.22.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST9146853SS  
revision: YS09  
compliance: SPC-4  
user capacity: 146,815,733,760 bytes [146 GB]  
logical block size: 512 bytes  
rotation rate: 15000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c5006b19d17b  
serial number: 6XM30AEG  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Mon Feb 17 05:32:25 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 62054:17  
manufactured in week 32 of year 2013  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 7  
elements in grown defect list: 288

vendor (seagate cache) information

blocks sent to initiator = 1135107145  
blocks received from initiator = 2066684678  
blocks read from cache and sent to initiator = 42839123  
number of read and write commands whose size <= segment size = 931304970  
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 62054.28  
number of minutes until next internal smart test = 11

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	914498143	1	0	914498144	1	359.786	0
write:	0	0	0	0	1	126927.137	0
verify:	2039721808	1	0	2039721809	1	63164.135	0

non-medium error count: 553

no self-tests have been logged