



Model: SEAGATE ST3146356SS

S/N: 3QN0KYKX

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST3146356SS**

Serial: **3QN0KYKX**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/17 05:13:21**

End time: **2025/02/17 06:12:31**

Duration: **00:59:10**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **124 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3146356SS
S/N: 3QN0KYKX



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST3146356SS
revision: HS10
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 3.5 inches
logical unit id: 0x5000c5000f78802f
serial number: 3QN0KYKX
device type: disk
transport protocol: SAS (SPL-3)
local time is: Mon Feb 17 06:12:33 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 38 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 24797:35
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1276507594
blocks received from initiator = 2857274486
blocks read from cache and sent to initiator = 3309562
number of read and write commands whose size <= segment size = 392813708
number of read and write commands whose size > segment size = 834129

vendor (seagate/hitachi) factory information

number of hours powered up = 24797.58
number of minutes until next internal smart test = 0

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/ rewrites	errors corrected	algorithm invocations	processed [10^9 bytes]	uncorrected errors
	fast	delayed					
read:	35252188	0	0	35252188	35252188	153.108	0
write:	0	0	0	0	0	23629.599	0
verify:	13689839	0	0	13689839	13689839	9243.487	0

non-medium error count: 113

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	2	5	-	[- - -]
# 2	background short	completed	2	5	-	[- - -]

long (extended) self-test duration: 1740 seconds [29.0 minutes]