



Model: SEAGATE ST4000NM0025

S/N: ZC19XDV00000C930GJ3D

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST4000NM0025**

Serial: **ZC19XDV00000C930GJ3D**

Size(Apparent): **4000 GB, 4000787030016 bytes**

Bus: **SAS**

Size(Real): **4000 GB, 4000787030016 bytes**

Disk Erasure Details

Start time: **2025/02/16 10:37:22**

End time: **2025/02/17 06:42:40**

Duration: **20:05:18**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **4000787030016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **165 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST4000NM0025

S/N: ZC19XDV00000C930GJ3D

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST4000NM0025
revision: N004
compliance: SPC-4
user capacity: 4,000,787,030,016 bytes [4.00 TB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x5000c500a7edc627
serial number: ZC19XDV00000C930GJ3D
device type: disk
transport protocol: SAS (SPL-3)
local time is: Mon Feb 17 06:42:42 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned <not available>
power on minutes since format <not available>
current drive temperature: 35 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 28564:48
manufactured in week 06 of year 2019
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 71
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 1264
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 3522703393
blocks received from initiator = 2743174088
blocks read from cache and sent to initiator = 348670
number of read and write commands whose size <= segment size = 55074
number of read and write commands whose size > segment size = 9225

vendor (seagate/hitachi) factory information


number of hours powered up = 28564.80
number of minutes until next internal smart test = 16

error counter log:

| | errors corrected by ecc | fast delayed | rereads/rewrites | total errors corrected | correction algorithm invocations | gigabytes processed [10^9 bytes] | total uncorrected errors |
|---------|-------------------------|----------------|------------------|------------------------|----------------------------------|----------------------------------|--------------------------|
| read: | 1456018027 | 0 | 0 | 1456018027 | 0 | 4001.758 | 0 |
| write: | 0 | 0 | 0 | 0 | 0 | 8001.591 | 0 |
| verify: | 2805051 | 0 | 0 | 2805051 | 0 | 0.890 | 0 |

non-medium error count: 0

[gltsd (global logging target save disable) set. enable save with '-s on']
no self-tests have been logged



Model: SEAGATE ST4000NM0025
S/N: ZC19XDV00000C930GJ3D

Disk Erasure Report

Page 3 - Smart Data

