



Model: SEAGATE XS400LE10003

S/N: ZD40135L0000822150Z3

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE XS400LE10003**

Serial: **ZD40135L0000822150Z3**

Size(Apparent): **400 GB, 400088457216 bytes**

Bus: **SAS-SSD**

Size(Real): **400 GB, 400088457216 bytes**

Disk Erasure Details

Start time: **2025/02/17 04:46:51**

End time: **2025/02/17 08:56:46**

Duration: **04:09:55**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **400088457216, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **80 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE XS400LE10003

S/N: ZD40135L0000822150Z3

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: XS400LE10003
revision: 0005
compliance: SPC-5
user capacity: 400,088,457,216 bytes [400 GB]
logical block size: 512 bytes
physical block size: 4096 bytes
lu is resource provisioned, lbprz=1
rotation rate: Solid State Device
form factor: 2.5 inches
logical unit id: 0x5000c500bb398727
serial number: ZD40135L0000822150Z3
device type: disk
transport protocol: SAS (SPL-3)
local time is: Mon Feb 17 08:57:17 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

percentage used endurance indicator: 2%
current drive temperature: 33 C
drive trip temperature: 70 C

accumulated power on time, hours:minutes 43141:07
manufactured in week 26 of year 2019
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 34
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 916320782
blocks received from initiator = 1516743496
blocks read from cache and sent to initiator = 0
number of read and write commands whose size <= segment size = 0
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 43141.12
number of minutes until next internal smart test = 50

error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	0	0	0	0	4867.203	0
write:	0	0	0	0	13986.709	0

non-medium error count: 0

no self-tests have been logged