



Model: HGST HUS726040ALS214

S/N: K4J058PB

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HGST HUS726040ALS214**

Serial: **K4J058PB**

Size(Apparent): **4000 GB, 4000787030016 bytes**

Bus: **SAS**

Size(Real): **4000 GB, 4000787030016 bytes**

Disk Erasure Details

Start time: **2025/02/16 01:53:27**

End time: **2025/02/17 12:11:43**

Duration: **34:18:16**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **4000787030016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **97 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HGST HUS726040ALS214

S/N: K4J058PB

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HGST
product: HUS726040ALS214
revision: KJ03
compliance: SPC-4
user capacity: 4,000,787,030,016 bytes [4.00 TB]
logical block size: 512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
lu is fully provisioned
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x5000cca25d710b50
serial number: K4J058PB
device type: disk
transport protocol: SAS (SPL-3)
local time is: Mon Feb 17 12:11:44 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: FIRMWARE IMPENDING FAILURE DATA ERROR RATE TOO HIGH [asc=5d, ascq=62]

current drive temperature: 34 C
drive trip temperature: 50 C

accumulated power on time, hours:minutes 4676:02
manufactured in week 05 of year 2017
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 36
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 2714
elements in grown defect list: 0

vendor (seagate cache) information
blocks sent to initiator = 15146675454607360

error counter log:

	errors corrected by		total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors	
	ecc	rereads/ rewrites					
	fast	delayed					
read:	0	16761	0	175749	12333395	45044.627	11
write:	0	26	0	69	320273	52921.925	0
verify:	0	3655	0	37585	8003936	4471.977	82

non-medium error count: 0

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	80	3	-	[- - -]
# 2	reserved(7)	completed	64	2	-	[- - -]

long (extended) self-test duration: 34237 seconds [570.6 minutes]