



Model: SEAGATE ST3146356SS
S/N: 3QN1W8NK

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST3146356SS**

Serial: **3QN1W8NK**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/17 14:15:15**

End time: **2025/02/17 15:17:29**

Duration: **01:02:14**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **117 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3146356SS
S/N: 3QN1W8NK



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST3146356SS
revision: HS09
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15015 rpm
logical unit id: 0x5000c500137019d7
serial number: 3QN1W8NK
device type: disk
transport protocol: SAS (SPL-3)
local time is: Mon Feb 17 15:17:36 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 34 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 46543:39
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 3832302128
blocks received from initiator = 2234733341
blocks read from cache and sent to initiator = 2426631435
number of read and write commands whose size <= segment size = 25698164
number of read and write commands whose size > segment size = 11029409

vendor (seagate/hitachi) factory information

number of hours powered up = 46543.65
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by ecc	fast delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	2183759991	42	0	2183760033	2183760033	228981.646	0
write:	0	0	0	0	0	349706.698	0
verify:	63765498	0	0	63765498	63765498	32460.855	0

non-medium error count: 252

no self-tests have been logged