



Model: HITACHI HUS153014VLS300

S/N: J4V8DABC

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HITACHI HUS153014VLS300**

Serial: **J4V8DABC**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/17 22:17:40**

End time: **2025/02/17 23:36:34**

Duration: **01:18:54**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **93 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HITACHI HUS153014VLS300

S/N: J4V8DABC

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HITACHI
product: HUS153014VLS300
revision: A280
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
logical unit id: 0x5000cca0050f4514
serial number: J4V8DABC
device type: disk
transport protocol: SAS (SPL-3)
local time is: Mon Feb 17 23:36:35 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 35 C
drive trip temperature: 85 C

accumulated power on time, hours:minutes 10685:04
manufactured in week 41 of year 2007
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 58
elements in grown defect list: 0

vendor (seagate cache) information
blocks sent to initiator = 46173186408054784

error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	0 21574685	0	21574685	44299226	113192.086	0
write:	0 9307968	0	9307968	9319958	106050.378	0
verify:	0 352171	0	352171	362859	83713.975	0

non-medium error count: 6

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	-	0	-	[- - -]
# 2	background short	completed	-	0	-	[- - -]

long (extended) self-test duration: 6422 seconds [107.0 minutes]