



Model: MAXTOR ATLAS10K5_147SAS

S/N: J4H18R3K

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **MAXTOR ATLAS10K5_147SAS**

Serial: **J4H18R3K**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/17 22:17:41**

End time: **2025/02/18 00:13:21**

Duration: **01:55:40**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **63 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: MAXTOR ATLAS10K5_147SAS

S/N: J4H18R3K

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: MAXTOR
product: ATLAS10K5_147SAS
revision: BP00
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 10002 rpm
logical unit id: 0x50010b90002e0950
serial number: J4H18R3K
device type: disk
transport protocol: SAS (SPL-3)
local time is: Tue Feb 18 00:13:24 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

grown defects during certification = 0
total blocks reassigned during format = 0
total new blocks reassigned = 8
power on minutes since format = 6799260
current drive temperature: 34 C
drive trip temperature: 0 C

accumulated power on time, hours:minutes 113321:31
accumulated start-stop cycles: 127
elements in grown defect list: 6

error counter log:

	errors corrected by		total errors		correction algorithm	gigabytes processed	total uncorrected errors
	ecc	rereads/rewrites	corrected		invocations	[10^9 bytes]	
read:	2347684579	14494	0	0	0	289491.559	0
write:	0	66	0	0	0	130515.086	0

non-medium error count: 95

last n error events log page

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	-	1	-	[- - -]
# 2	background short	completed	-	0	-	[- - -]

long (extended) self-test duration: 2880 seconds [48.0 minutes]