



Model: SEAGATE ST2000NM0001  
S/N: Z1P0CV1C



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST2000NM0001**

Serial: **Z1P0CV1C**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

## Disk Erasure Details

Start time: **2025/02/17 14:16:25**

End time: **2025/02/18 05:34:14**

Duration: **15:17:49**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **108 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST2000NM0001

S/N: Z1P0CV1C

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST2000NM0001  
revision: PS04  
compliance: SPC-4  
user capacity: 2,000,398,934,016 bytes [2.00 TB]  
logical block size: 512 bytes  
rotation rate: 7200 rpm  
form factor: 3.5 inches  
logical unit id: 0x5000c50034f75a9f  
serial number: Z1P0CV1C  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Tue Feb 18 05:34:15 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 36676:32  
manufactured in week 36 of year 2011  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 7  
elements in grown defect list: 3

vendor (seagate cache) information

blocks sent to initiator = 2129788610  
blocks received from initiator = 76448768  
blocks read from cache and sent to initiator = 637872218  
number of read and write commands whose size <= segment size = 44206782  
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 36676.53  
number of minutes until next internal smart test = 14

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	4231581174	0	0	4231581174	0	22109.462	0
write:	0	0	0	0	0	11154.327	0
verify:	1600398304	0	0	1600398304	0	23236.333	0

non-medium error count: 33

no self-tests have been logged