



Model: SEAGATE ST32000444SS
S/N: 9WM6R4XD



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST32000444SS**

Serial: **9WM6R4XD**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

Disk Erasure Details

Start time: **2025/02/17 22:14:13**

End time: **2025/02/18 14:40:47**

Duration: **16:26:34**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **101 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST32000444SS

S/N: 9WM6R4XD

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST32000444SS
revision: KS68
compliance: SPC-3
user capacity: 2,000,398,934,016 bytes [2.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x5000c500349145c3
serial number: 9WM6R4XD
device type: disk
transport protocol: SAS (SPL-3)
local time is: Tue Feb 18 14:40:49 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 37831:30
manufactured in week 27 of year 2011
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 19
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 19
elements in grown defect list: 243

vendor (seagate cache) information

blocks sent to initiator = 3616563179
blocks received from initiator = 2985346646
blocks read from cache and sent to initiator = 2772052299
number of read and write commands whose size <= segment size = 149246340
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 37831.50
number of minutes until next internal smart test = 60


error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	1054827837	8201	0	1054836038	41202.659	2
write:	0	0	0	0	14808.946	0
verify:	1516806553	1	0	1516806554	34518.164	0

non-medium error count: 92

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	16	26	-	[- - -]
# 2	background short	completed	16	24	-	[- - -]
# 3	background long	completed	16	3	-	[- - -]
# 4	background short	completed	16	0	-	[- - -]



Model: SEAGATE ST32000444SS
S/N: 9WM6R4XD

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 18500 seconds [308.3 minutes]