



Model: Micron_1300_MTFD

S/N: 21032CBF9BD9

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **Micron_1300_MTFD**

Serial: **21032CBF9BD9**

Size(Apparent): **2048 GB, 2048408248320 bytes**

Bus: **ATA-SSD**

Size(Real): **2048 GB, 2048408248320 bytes**

Disk Erasure Details

Start time: **2025/02/20 11:32:14**

End time: **2025/02/20 20:22:05**

Duration: **08:49:51**

Status: **ERASED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **2048408248320, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **No hidden sectors**

HPA/DCO Size: **No hidden sectors**

Errors(pass/sync/verify): **0/0/0**

Throughput: **193 MB/sec**

Information:

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: Micron_1300_MTFD

S/N: 21032CBF9BD9

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

model family: Crucial/Micron Client SSDs
device model: Micron_1300_MTFDDAK2T0TDL
serial number: 21032CBF9BD9
lu wwn device id: 5 00a075 12cbf9bd9
firmware version: M5MU030
user capacity: 2,048,408,248,320 bytes [2.04 TB]
sector size: 512 bytes logical/physical
rotation rate: Solid State Device
form factor: 2.5 inches
trim command: Available, deterministic, zeroed
device is: In smartctl database [for details use: -P show]
ata version is: ACS-4 T13/BSR INCITS 529 revision 5
sata version is: SATA 3.3, 6.0 Gb/s (current: 6.0 Gb/s)
local time is: Thu Feb 20 20:22:07 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled

=== start of read smart data section ===

smart overall-health self-assessment test result: PASSED

general smart values:

offline data collection status: (0x00)Offline data collection activity
was never started.
auto offline data collection: Disabled.
self-test execution status: (0)The previous self-test routine completed
without error or no self-test has ever
been run.
total time to complete offline
data collection: (5428) seconds.
offline data collection
capabilities: (0x7b) SMART execute Offline immediate.
auto offline data collection on/off support.
suspend offline collection upon new
command.
offline surface scan supported.
self-test supported.
conveyance self-test supported.
selective self-test supported.
smart capabilities: (0x0003)Saves SMART data before entering
power-saving mode.
supports smart auto save timer.
error logging capability: (0x01)Error logging supported.
general purpose logging supported.
short self-test routine
recommended polling time: (2) minutes.
extended self-test routine
recommended polling time: (24) minutes.
conveyance self-test routine
recommended polling time: (3) minutes.
sct capabilities: (0x0035)SCT Status supported.
sct feature control supported.
sct data table supported.

smart attributes data structure revision number: 16

vendor specific smart attributes with thresholds:

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
1	raw_read_error_rate	0x002f	100	100	000	pre-fail	always	-	12
5	reallocate_nand_blk_cnt	0x0032	100	100	010	old_age	always	-	1
9	power_on_hours	0x0032	100	100	000	old_age	always	-	26842
12	power_cycle_count	0x0032	100	100	000	old_age	always	-	20



Model: Micron_1300_MTFD

S/N: 21032CBF9BD9

Disk Erasure Report

Page 3 - Smart Data



171	program_fail_count	0x0032	100	100	000	old_age	always	-	1
172	erase_fail_count	0x0032	100	100	000	old_age	always	-	0
173	ave_block-erase_count	0x0032	086	086	000	old_age	always	-	80
174	unexpect_power_loss_ct	0x0032	100	100	000	old_age	always	-	18
183	sata_interfac_downshift	0x0032	100	100	000	old_age	always	-	0
184	error_correction_count	0x0032	100	100	000	old_age	always	-	0
187	reported_uncorrect	0x0032	100	100	000	old_age	always	-	0
194	temperature_celsius	0x0022	059	047	000	old_age	always	-	41 (min/max 17/53)
196	reallocated_event_count	0x0032	100	100	000	old_age	always	-	1
197	current_pending_ecc_cnt	0x0032	100	100	000	old_age	always	-	0
198	offline_uncorrectable	0x0030	100	100	000	old_age	offline	-	0
199	udma_crc_error_count	0x0032	100	100	000	old_age	always	-	0
202	percent_lifetime_remain	0x0030	086	086	001	old_age	offline	-	14
206	write_error_rate	0x000e	100	100	000	old_age	always	-	1
246	total_lbas_written	0x0032	100	100	000	old_age	always	-	138381389587
247	host_program_page_count	0x0032	100	100	000	old_age	always	-	4325057102
248	ftl_program_page_count	0x0032	100	100	000	old_age	always	-	5567998697
180	unused_reserve_nand_blk	0x0033	000	000	000	pre-fail	always	-	4083
210	success_rain_recov_cnt	0x0032	100	100	000	old_age	always	-	48

smart error log version: 1
no errors logged

smart self-test log structure revision number 1

num	test_description	status	remaining	lifetime(hours)	lba_of_first_error
# 1	vendor (0xff)	completed without error	00%	26821	-
# 2	vendor (0xff)	completed without error	00%	25911	-
# 3	vendor (0xff)	completed without error	00%	24496	-
# 4	vendor (0xff)	completed without error	00%	23067	-
# 5	vendor (0xff)	completed without error	00%	21635	-
# 6	vendor (0xff)	completed without error	00%	21029	-
# 7	vendor (0xff)	completed without error	00%	19679	-
# 8	vendor (0xff)	completed without error	00%	18216	-
# 9	vendor (0xff)	completed without error	00%	16632	-
#10	vendor (0xff)	completed without error	00%	16389	-
#11	vendor (0xff)	completed without error	00%	13147	-
#12	vendor (0xff)	completed without error	00%	12370	-
#13	vendor (0xff)	completed without error	00%	9092	-
#14	vendor (0xff)	completed without error	00%	8520	-
#15	vendor (0xff)	completed without error	00%	5448	-
#16	vendor (0xff)	completed without error	00%	3334	-
#17	vendor (0xff)	completed without error	00%	1682	-
#18	vendor (0xff)	completed without error	00%	192	-
#19	vendor (0xff)	completed without error	00%	143	-

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
1	0	0	not_testing
2	0	0	not_testing
3	0	0	not_testing
4	0	0	not_testing
5	0	0	not_testing

selective self-test flags (0x0):

after scanning selected spans, do not read-scan remainder of disk.

if selective self-test is pending on power-up, resume after 0 minute delay.