



Model: SEAGATE ST3146755SS
S/N: 3LN0GSET



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST3146755SS**

Serial: **3LN0GSET**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/21 17:05:22**

End time: **2025/02/21 18:46:30**

Duration: **01:41:08**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **72 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3146755SS
S/N: 3LN0GSET



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST3146755SS
revision: T106
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15015 rpm
logical unit id: 0x5000c5000231ed23
serial number: 3LN0GSET
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Feb 21 18:46:31 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 34 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 39499:05
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 512396962
blocks received from initiator = 1176576678
blocks read from cache and sent to initiator = 734530923
number of read and write commands whose size <= segment size = 1704522915
number of read and write commands whose size > segment size = 49311273

vendor (seagate/hitachi) factory information

number of hours powered up = 39499.08
number of minutes until next internal smart test = 20

error counter log:

	errors corrected by		total	correction	gigabytes	total	
	ecc	rereads/	errors	algorithm	processed	uncorrected	
	fast delayed	rewrites	corrected	invocations	[10^9 bytes]	errors	
read:	1429419543	11	0	1429419554	1429419554	217787.008	0
write:	0	0	4	4	5	29267106.784	1
verify:	801017288	0	0	801017288	801017288	101572.362	0

non-medium error count: 119

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	-	9	-	[- - -]
# 2	background short	completed	-	9	-	[- - -]
# 3	background long	completed	-	8	-	[- - -]
# 4	background short	completed	-	7	-	[- - -]
# 5	background long	completed	-	1	-	[- - -]
# 6	background short	completed	-	0	-	[- - -]

long (extended) self-test duration: 1941 seconds [32.4 minutes]