

Model: Pliant LB150S

S/N: 20001504



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **Pliant LB150S**

Serial: **20001504**

Size(Apparent): **149 GB, 149039751168 bytes**

Bus: **SAS-SSD**

Size(Real): **149 GB, 149039751168 bytes**

Disk Erasure Details

Start time: **2025/02/22 06:30:32**

End time: **2025/02/22 07:14:14**

Duration: **00:43:42**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **149039751168, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **170 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: Pliant LB150S

S/N: 20001504



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: Pliant
product: LB150S
revision: D012
compliance: SPC-3
user capacity: 149,039,751,168 bytes [149 GB]
logical block size: 512 bytes
rotation rate: Solid State Device
form factor: 2.5 inches
logical unit id: 0x5001e820013132e0
serial number: 20001504
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 07:14:15 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

percentage used endurance indicator: 0%
current drive temperature: 24 C
drive trip temperature: <not available>

accumulated power on time, hours:minutes 2:07
manufactured in week 48 of year 2009
specified cycle count over device lifetime: 0
accumulated start-stop cycles: 25
error counter log:

	errors corrected by		total	correction	gigabytes	total
	ecc		errors	algorithm	processed	uncorrected
	fast	delayed	rereads/ rewrites	invocations	[10^9 bytes]	errors
read:	0	0	0	0	182921.302	0
write:	0	0	0	0	3705671.613	0
verify:	0	0	0	0	92406.136	0

non-medium error count: 0

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	-	2	-	[- - -]
# 2	background long	completed	-	1	-	[- - -]
# 3	background short	completed	-	0	-	[- - -]

long (extended) self-test duration: 280 seconds [4.7 minutes]