



Model: SEAGATE ST9146853SS
S/N: 6XM26EJC



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **SEAGATE ST9146853SS**

Serial: **6XM26EJC**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/22 06:27:17**

End time: **2025/02/22 07:21:17**

Duration: **00:54:00**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **135 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST9146853SS

S/N: 6XM26EJC

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9146853SS
revision: YS09
compliance: SPC-4
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5005f30239b
serial number: 6XM26EJC
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 07:21:18 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 37 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 67176:01
manufactured in week 04 of year 2013
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 27
elements in grown defect list: 270

vendor (seagate cache) information

blocks sent to initiator = 2692036632
blocks received from initiator = 3827584014
blocks read from cache and sent to initiator = 48698755
number of read and write commands whose size <= segment size = 935609729
number of read and write commands whose size > segment size = 49

vendor (seagate/hitachi) factory information

number of hours powered up = 67176.02
number of minutes until next internal smart test = 5

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	891526046	0	0	891526046	0	739.494	0
write:	0	0	0	0	2	132261.297	1
verify:	658490470	8	0	658490478	8	65681.814	0

non-medium error count: 30

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	32	2	-	[- - -]
# 2	background long	completed	32	1	-	[- - -]
# 3	background short	completed	32	1	-	[- - -]

long (extended) self-test duration: 1099 seconds [18.3 minutes]