



Model: HP DG072BB975
S/N: 3NP3EDDK00009914TUA1



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **HP DG072BB975**

Serial: **3NP3EDDK00009914TUA1**

Size(Apparent): **73 GB, 73407865856 bytes**

Bus: **SAS**

Size(Real): **73 GB, 73407865856 bytes**

Disk Erasure Details

Start time: **2025/02/22 06:28:53**

End time: **2025/02/22 07:27:06**

Duration: **00:58:13**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **73407865856, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **63 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: HP DG072BB975
S/N: 3NP3EDDK00009914TUA1



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HP
product: DG072BB975
revision: HPDC
compliance: SPC-3
user capacity: 73,407,865,856 bytes [73.4 GB]
logical block size: 512 bytes
rotation rate: 10033 rpm
logical unit id: 0x5000c5000c5a67f7
serial number: 3NP3EDDK00009914TUA1
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 07:27:13 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

current drive temperature: 38 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 36686:04
elements in grown defect list: 0

error counter log:

	errors corrected by		rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
	ecc	fast delayed					
read:	0	0	0	0	0	0.000	0
write:	0	0	0	0	0	0.000	0

non-medium error count: 0

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err [sk asc asq]
# 1	background long	completed	-	0	- [- - -]
# 2	background short	completed	-	0	- [- - -]

long (extended) self-test duration: 1070 seconds [17.8 minutes]