



Model: TOSHIBA MK1401GRRB

S/N: 15L0A10NFQ86

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **TOSHIBA MK1401GRRB**

Serial: **15L0A10NFQ86**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

## Disk Erasure Details

Start time: **2025/02/22 06:26:13**

End time: **2025/02/22 07:37:47**

Duration: **01:11:34**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **102 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA MK1401GRRB

S/N: 15L0A10NFQ86

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: TOSHIBA  
product: MK1401GRRB  
revision: DB08  
compliance: SPC-4  
user capacity: 146,815,733,760 bytes [146 GB]  
logical block size: 512 bytes  
rotation rate: 15000 rpm  
form factor: 2.5 inches  
logical unit id: 0x50000396082297f4  
serial number: 15L0A10NFQ86  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sat Feb 22 07:37:58 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C  
drive trip temperature: 65 C

accumulated power on time, hours:minutes 79393:38  
manufactured in week 04 of year 2015  
specified cycle count over device lifetime: 50000  
accumulated start-stop cycles: 20  
specified load-unload count over device lifetime: 200000  
accumulated load-unload cycles: 3505  
elements in grown defect list: 0

error counter log:

	errors corrected by		total	correction	gigabytes	total
	ecc	rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10 <sup>9</sup> bytes] errors
read:	0	8	8	34	1489346.851	0
write:	0	15	15	34	171253.710	0
verify:	0	0	0	0	69582.269	0

non-medium error count: 18

no self-tests have been logged