

Model: SEAGATE ST973401SS

S/N: 3LB0P4HX

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

## Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

## Disk Information

Make/Model: **SEAGATE ST973401SS**

Serial: **3LB0P4HX**

Size(Apparent): **73 GB, 73407820800 bytes**

Bus: **SAS**

Size(Real): **73 GB, 73407820800 bytes**

## Disk Erasure Details

Start time: **2025/02/22 06:28:42**

End time: **2025/02/22 07:44:08**

Duration: **01:15:26**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **73407820800, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **48 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST973401SS

S/N: 3LB0P4HX

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST973401SS  
revision: S108  
compliance: SPC-3  
user capacity: 73,407,820,800 bytes [73.4 GB]  
logical block size: 512 bytes  
rotation rate: 10033 rpm  
logical unit id: 0x5000c50000d09f2b  
serial number: 3LB0P4HX  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sat Feb 22 07:44:15 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 42 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 155907:05  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 296661925  
blocks received from initiator = 2550556970  
blocks read from cache and sent to initiator = 3641986177  
number of read and write commands whose size <= segment size = 3217937518  
number of read and write commands whose size > segment size = 63028

vendor (seagate/hitachi) factory information

number of hours powered up = 155932.57  
number of minutes until next internal smart test = 120

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	26600350	0	0	26600350	26600350	50863.034	0
write:	0	0	0	0	0	29134.287	0
verify:	498252	0	0	498252	498252	47641.158	0

non-medium error count: 15

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	-	1	-	[- - -]
# 2	background short	completed	-	1	-	[- - -]

long (extended) self-test duration: 1560 seconds [26.0 minutes]