



Model: SEAGATE ST3450857SS  
S/N: 3SK0QMER

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST3450857SS**

Serial: **3SK0QMER**

Size(Apparent): **450 GB, 450098159616 bytes**

Bus: **SAS**

Size(Real): **450 GB, 450098159616 bytes**

## Disk Erasure Details

Start time: **2025/02/22 06:23:21**

End time: **2025/02/22 08:51:28**

Duration: **02:28:07**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **450098159616, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **151 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST3450857SS  
S/N: 3SK0QMER



# Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST3450857SS  
revision: ES62  
compliance: SPC-3  
user capacity: 450,098,159,616 bytes [450 GB]  
logical block size: 512 bytes  
rotation rate: 15015 rpm  
logical unit id: 0x5000c500231046d3  
serial number: 3SK0QMER  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sat Feb 22 08:51:30 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 37 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 39972:17  
elements in grown defect list: 65

vendor (seagate cache) information

blocks sent to initiator = 4034457034  
blocks received from initiator = 330443989  
blocks read from cache and sent to initiator = 483661779  
number of read and write commands whose size <= segment size = 1259479998  
number of read and write commands whose size > segment size = 2207445

vendor (seagate/hitachi) factory information

number of hours powered up = 39972.28  
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by	total	correction	gigabytes	total		
	ecc	rereads/	errors	processed	uncorrected		
	fast   delayed	rewrites	corrected	invocations	[10^9 bytes] errors		
read:	1462577881	48	0	1462577929	1462577929	377653.802	0
write:	0	0	0	0	0	11339.035	0
verify:	734552211	18	0	734552229	734552276	30797.351	47

non-medium error count: 17375

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
			number	(hours)		
# 1	background long	completed	16	1	-	[- - -]
# 2	background short	completed	16	0	-	[- - -]

long (extended) self-test duration: 4800 seconds [80.0 minutes]