



Model: HITACHI HUS156060VLS600

S/N: LXW9ER6J

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HITACHI HUS156060VLS600**

Serial: **LXW9ER6J**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/22 06:24:47**

End time: **2025/02/22 09:54:03**

Duration: **03:29:16**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **143 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HITACHI HUS156060VLS600

S/N: LXW9ER6J

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HITACHI
product: HUS156060VLS600
revision: E516
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 15030 rpm
form factor: 3.5 inches
logical unit id: 0x5000cca02a498954
serial number: LXW9ER6J
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 09:54:05 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 38 C
drive trip temperature: 85 C

accumulated power on time, hours:minutes 40223:40
manufactured in week 21 of year 2012
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 17
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 112074392007081984

error counter log:

	errors corrected by		total	correction	gigabytes	total	
	ecc		errors	algorithm	processed	uncorrected	
	fast	delayed	corrected	invocations	[10 ⁹ bytes]	errors	
read:	0	3335873	0	3335873	8053849	39334.816	0
write:	0	34406299	0	34406299	25430044	257977.674	0
verify:	0	677480	0	677480	230497	356500.345	1

non-medium error count: 3

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk	asc	asq]
	description		number	(hours)				
# 1	background short	completed	16	7		-	-	-
# 2	background short	completed	16	6		-	-	-
# 3	background short	completed	16	6		-	-	-
# 4	background short	completed	16	5		-	-	-

long (extended) self-test duration: 4981 seconds [83.0 minutes]