



Model: INTEL SSDSC2BB16
S/N: PHWL449400TE160MGN



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **INTEL SSDSC2BB16**

Serial: **PHWL449400TE160MGN**

Size(Apparent): **160 GB, 160041885696 bytes**

Bus: **ATA-SSD**

Size(Real): **160 GB, 160041885696 bytes**

Disk Erasure Details

Start time: **2025/02/22 11:40:42**

End time: **2025/02/22 12:29:57**

Duration: **00:49:15**

Status: **ERASED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **160041885696, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **No hidden sectors**

HPA/DCO Size: **No hidden sectors**

Errors(pass/sync/verify): **0/0/0**

Throughput: **162 MB/sec**

Information:

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: INTEL SSDSC2BB16
S/N: PHWL449400TE160MGN



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

```
=== start of information section ===
model family:      Intel 730 and DC S35x0/3610/3700 Series SSDs
device model:      INTEL SSDSC2BB160G4T
serial number:     PHWL449400TE160MGN
lu wwn device id:  5 5cd2e4 04c46e3a1
add. product id:   DELL(tm)
firmware version:  D201DL13
user capacity:     160,041,885,696 bytes [160 GB]
sector sizes:      512 bytes logical, 4096 bytes physical
rotation rate:     Solid State Device
form factor:       2.5 inches
trim command:      Available, deterministic, zeroed
device is:         In smartctl database [for details use: -P show]
ata version is:    ACS-2 T13/2015-D revision 3
sata version is:   SATA 2.6, 6.0 Gb/s (current: 3.0 Gb/s)
local time is:     Sat Feb 22 12:30:07 2025 GMT
smart support is:  Available - device has SMART capability.
smart support is:  Enabled
```

```
=== start of read smart data section ===
smart overall-health self-assessment test result: PASSED
```

```
general smart values:
offline data collection status: (0x02)Offline data collection activity
was completed without error.
auto offline data collection: Disabled.
self-test execution status:      ( 0)The previous self-test routine completed
without error or no self-test has ever
been run.
total time to complete offline
data collection: ( 2) seconds.
offline data collection
capabilities: (0x79) SMART execute Offline immediate.
no auto offline data collection support.
suspend offline collection upon new
command.
offline surface scan supported.
self-test supported.
conveyance self-test supported.
selective self-test supported.
smart capabilities:              (0x0003)Saves SMART data before entering
power-saving mode.
supports smart auto save timer.
error logging capability:        (0x01)Error logging supported.
general purpose logging supported.
short self-test routine
recommended polling time: ( 1) minutes.
extended self-test routine
recommended polling time: ( 60) minutes.
conveyance self-test routine
recommended polling time: ( 60) minutes.
sct capabilities:                (0x003d)SCT Status supported.
sct error recovery control supported.
sct feature control supported.
sct data table supported.
```

```
smart attributes data structure revision number: 1
vendor specific smart attributes with thresholds:
```

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
1	raw_read_error_rate	0x000f	130	130	039	pre-fail	always	-	311342048
5	reallocated_sector_ct	0x0033	100	100	001	pre-fail	always	-	0



Model: INTEL SSDSC2BB16
S/N: PHWL449400TE160MGN



Disk Erasure Report

Page 3 - Smart Data

9	power_on_hours	0x0032	100	100	000	old_age	always	-	12510
12	power_cycle_count	0x0032	100	100	000	old_age	always	-	25
13	read_soft_error_rate	0x0032	123	100	000	old_age	always	-	4606309344
179	used_rsvd_blk_cnt_tot	0x0033	100	100	010	pre-fail	always	-	0
180	unused_rsvd_blk_cnt_tot	0x0032	100	100	000	old_age	always	-	2309
181	program_fail_cnt_total	0x003a	100	100	000	old_age	always	-	0
182	erase_fail_count_total	0x003a	100	100	000	old_age	always	-	0
184	end-to-end_error	0x0032	100	100	000	old_age	always	-	0
194	temperature_internal	0x0022	100	100	000	old_age	always	-	37
195	hardware_ecc_recovered	0x0032	100	100	000	old_age	always	-	0
198	offline_uncorrectable	0x0010	100	100	000	old_age	offline	-	0
199	crc_error_count	0x003e	100	100	000	old_age	always	-	0
201	unknown_ssd_attribute	0x0033	100	100	010	pre-fail	always	-	347895562890
226	workld_media_wear_indic	0x0032	100	100	000	old_age	always	-	26173
227	workld_host_reads_perc	0x0032	100	100	000	old_age	always	-	62
228	workload_minutes	0x0032	100	100	000	old_age	always	-	750360
233	media_wearout_indicator	0x0032	100	100	000	old_age	always	-	2548873
245	unknown_attribute	0x0032	075	075	000	old_age	always	-	0

smart error log version: 1
no errors logged

smart self-test log structure revision number 1

num	test_description	status	remaining	lifetime(hours)	lba_of_first_error
# 1	short offline	completed without error	00%	2	-
# 2	extended offline	completed without error	00%	1	-
# 3	short offline	completed without error	00%	1	-

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
1	0	0	not_testing
2	0	0	not_testing
3	0	0	not_testing
4	0	0	not_testing
5	0	0	not_testing

selective self-test flags (0x0):

after scanning selected spans, do not read-scan remainder of disk.
if selective self-test is pending on power-up, resume after 0 minute delay.