



Model: SEAGATE ST9300653SS
S/N: 6XN37L71



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST9300653SS**

Serial: **6XN37L71**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

Disk Erasure Details

Start time: **2025/02/22 11:39:44**

End time: **2025/02/22 13:27:53**

Duration: **01:48:09**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **138 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9300653SS

S/N: 6XN37L71

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9300653SS
revision: YS0D
compliance: SPC-4
user capacity: 300,000,000,000 bytes [300 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5005fb21b7b
serial number: 6XN37L71
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 13:27:55 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: HARDWARE IMPENDING FAILURE GENERAL HARD DRIVE FAILURE [asc=5d, ascq=10]

current drive temperature: 34 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 22737:58
manufactured in week 10 of year 2013
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 74
elements in grown defect list: 54

vendor (seagate cache) information

blocks sent to initiator = 142276763
blocks received from initiator = 3373080044
blocks read from cache and sent to initiator = 842312130
number of read and write commands whose size <= segment size = 3868309310
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 22737.97
number of minutes until next internal smart test = 10

error counter log:

	errors corrected by	total errors	correction algorithm	gigabytes processed	total uncorrected errors		
	ecc	rereads/rewrites		[10^9 bytes]			
	fast delayed		corrected invocations				
read:	2927410472	50	0	2927410522	51	655772.418	1
write:	0	0	52	52	481374.962	0	
verify:	3683907699	9	0	3683907708	178	175080.247	169

non-medium error count: 47

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	32	11	-	[- - -]
# 2	background long	completed	32	11	-	[- - -]
# 3	background short	completed	32	9	-	[- - -]
# 4	background short	completed	32	4	-	[- - -]
# 5	background short	completed	32	1	-	[- - -]

long (extended) self-test duration: 2052 seconds [34.2 minutes]



Model: SEAGATE ST9300653SS

S/N: 6XN37L71

Disk Erasure Report

Page 3 - Smart Data

