



Model: SEAGATE ST1000NX0373

S/N: W473BABY0000E0514X4W

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST1000NX0373**

Serial: **W473BABY0000E0514X4W**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/02/22 06:24:18**

End time: **2025/02/22 14:35:38**

Duration: **08:11:20**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **101 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST1000NX0373

S/N: W473BABY0000E0514X4W

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST1000NX0373
revision: ET05
compliance: SPC-4
user capacity: 1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
physical block size: 4096 bytes
lu is fully provisioned
rotation rate: 7200 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500ddd0775b
serial number: W473BABY0000E0514X4W
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 14:35:39 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned <not available>
power on minutes since format <not available>
current drive temperature: 30 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 20495:40
manufactured in week 11 of year 2021
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 9
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 22056
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1956877312
blocks received from initiator = 3907050336
blocks read from cache and sent to initiator = 345200
number of read and write commands whose size <= segment size = 9460
number of read and write commands whose size > segment size = 387

vendor (seagate/hitachi) factory information


number of hours powered up = 20495.67
number of minutes until next internal smart test = 4

error counter log:

	errors corrected by		total	correction	gigabytes	total
	ecc		errors	algorithm	processed	uncorrected
	fast	delayed	corrected	invocations	[10 ⁹ bytes]	errors
read:	863899992	0	863899992	0	1000.967	0
write:	0	0	0	0	2000.414	0
verify:	816799	0	816799	0	0.954	0

non-medium error count: 1

[gltsd (global logging target save disable) set. enable save with '-s on']



Model: SEAGATE ST1000NX0373
S/N: W473BABY0000E0514X4W

Disk Erasure Report

Page 3 - Smart Data



no self-tests have been logged