



Model: SEAGATE ST600MM0088

S/N: S421BTE2

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST600MM0088**

Serial: **S421BTE2**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/22 11:40:22**

End time: **2025/02/22 15:21:16**

Duration: **03:40:54**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **135 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0088

S/N: S421BTE2

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST600MM0088
revision: TT31
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5009704362b
serial number: S421BTE2
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 15:21:17 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned = 1
power on minutes since format <not available>
current drive temperature: 32 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 72150:47
manufactured in week 16 of year 2016
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 10
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 3014
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 3711977285
blocks received from initiator = 3775101790
blocks read from cache and sent to initiator = 4087699062
number of read and write commands whose size <= segment size = 470489024
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 72150.78
number of minutes until next internal smart test = 26

error counter log:

	errors corrected by ecc	fast delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	1741719709	2	0	1741719711	2	1061426.808	0
write:	0	0	182	182	185	185232.448	2
verify:	2934517702	0	0	2934517702	0	262666.152	0

non-medium error count: 399

no self-tests have been logged



Model: SEAGATE ST600MM0088

S/N: S421BTE2

Disk Erasure Report

Page 3 - Smart Data

