



Model: SEAGATE ST9600204SS
S/N: 6WN0V9YJ



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST9600204SS**

Serial: **6WN0V9YJ**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/22 11:43:06**

End time: **2025/02/22 15:27:36**

Duration: **03:44:30**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/0**

Throughput: **89 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9600204SS
S/N: 6WN0V9YJ



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9600204SS
revision: FM0A
compliance: SPC-3
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5003b2511a7
serial number: 6WN0V9YJ
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 15:27:38 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: HARDWARE IMPENDING FAILURE GENERAL HARD DRIVE FAILURE [asc=5d, ascq=10]

current drive temperature: 34 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 35638:00
manufactured in week 23 of year 2011
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 15
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 15
elements in grown defect list: 3

vendor (seagate cache) information

blocks sent to initiator = 3906876739
blocks received from initiator = 3775654732
blocks read from cache and sent to initiator = 2234441089
number of read and write commands whose size <= segment size = 2845584402
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 35638.00
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	2629352463	463	0	2629352926	1085373.672	63
write:	0	0	6959	6962	322726.737	1
verify:	1481113237	65	0	1481113302	386493.306	0

non-medium error count: 31768

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	16	7	-	[- - -]
# 2	background long	completed	16	3	-	[- - -]
# 3	background short	completed	16	1	-	[- - -]

long (extended) self-test duration: 6176 seconds [102.9 minutes]



Model: SEAGATE ST9600204SS
S/N: 6WN0V9YJ

Disk Erasure Report

Page 3 - Smart Data

