



Model: SEAGATE ST91000640SS
S/N: 9XG1K6SX



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST91000640SS**

Serial: **9XG1K6SX**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/02/22 06:26:48**

End time: **2025/02/22 16:07:39**

Duration: **09:40:51**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **86 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST91000640SS

S/N: 9XG1K6SX

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST91000640SS
revision: AS0D
compliance: SPC-4
user capacity: 1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500419d029f
serial number: 9XG1K6SX
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 16:07:41 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 21967:07
manufactured in week 16 of year 2012
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 23
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 7187
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 54186501
blocks received from initiator = 149717734
blocks read from cache and sent to initiator = 2383297620
number of read and write commands whose size <= segment size = 141408508
number of read and write commands whose size > segment size = 3

vendor (seagate/hitachi) factory information

number of hours powered up = 21967.12
number of minutes until next internal smart test = 59

error counter log:


	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	1194887168	0	0	1194887168	0	34198.798
write:	0	0	0	0	24275.264	0
verify:	3268646691	0	0	3268646691	0	1013.317

non-medium error count: 467

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	32	65535	-	[- - -]
# 2	background short	completed	32	65535	-	[- - -]

long (extended) self-test duration: 12198 seconds [203.3 minutes]



Model: SEAGATE ST91000640SS
S/N: 9XG1K6SX

Disk Erasure Report

Page 3 - Smart Data

