



Model: SEAGATE ST9600205SS
S/N: 6XR10D2C



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **SEAGATE ST9600205SS**

Serial: **6XR10D2C**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/22 11:43:35**

End time: **2025/02/22 16:29:57**

Duration: **04:46:22**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **104 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST9600205SS
S/N: 6XR10D2C



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9600205SS
revision: CS09
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c50039771693
serial number: 6XR10D2C
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 16:29:59 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 39318:08
manufactured in week 11 of year 2011
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 6
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 4107
elements in grown defect list: 31

vendor (seagate cache) information

blocks sent to initiator = 1252790329
blocks received from initiator = 524910628
blocks read from cache and sent to initiator = 2561835386
number of read and write commands whose size <= segment size = 575833435
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 39318.13
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by			total	correction		gigabytes	total
	ecc	rereads/		errors	algorithm		processed	uncorrected
	fast	delayed	rewrites	corrected	invocations		[10^9 bytes]	errors
read:	1894121436	3	0	1894121439	3		50687.837	0
write:	0	0	8975	8975	8976		77538.151	1
verify:	2408666909	2	0	2408666911	3		321816.155	0

non-medium error count: 113

no self-tests have been logged