



Model: SEAGATE ST91000640SS
S/N: 9XG771H2



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST91000640SS**

Serial: **9XG771H2**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/02/22 06:30:12**

End time: **2025/02/22 16:34:13**

Duration: **10:04:01**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **82 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST91000640SS
S/N: 9XG771H2



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST91000640SS
revision: AS0D
compliance: SPC-4
user capacity: 1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500593005fb
serial number: 9XG771H2
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 16:34:15 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 777:12
manufactured in week 32 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 50
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 9392
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 2755169250
blocks received from initiator = 3214912473
blocks read from cache and sent to initiator = 2703092952
number of read and write commands whose size <= segment size = 2111207160
number of read and write commands whose size > segment size = 284

vendor (seagate/hitachi) factory information

number of hours powered up = 777.20
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc	rereads/	rewrites	errors	algorithm	processed	uncorrected
	fast	delayed		corrected	invocations	[10^9 bytes]	errors
read:	2886884345	0	0	2886884345	0	835119.988	0
write:	0	0	3	3	3	129483.190	0
verify:	553850739	0	0	553850739	0	103164.760	0

non-medium error count: 645

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	32	53145	- [- - -]	
# 2	background short	completed	32	53128	- [- - -]	

long (extended) self-test duration: 12198 seconds [203.3 minutes]



Model: SEAGATE ST91000640SS
S/N: 9XG771H2

Disk Erasure Report

Page 3 - Smart Data

