



Model: TOSHIBA AL13SEB600

S/N: Y4G0A0UJFRD3

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **TOSHIBA AL13SEB600**

Serial: **Y4G0A0UJFRD3**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/22 11:43:51**

End time: **2025/02/22 16:44:16**

Duration: **05:00:25**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **99 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: TOSHIBA AL13SEB600

S/N: Y4G0A0UJFRD3

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: TOSHIBA
product: AL13SEB600
revision: DE0D
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50000395e82067d5
serial number: Y4G0A0UJFRD3
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 16:44:25 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 37 C
drive trip temperature: 65 C

accumulated power on time, hours:minutes 66333:05
manufactured in week 46 of year 2014
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 41
specified load-unload count over device lifetime: 200000
accumulated load-unload cycles: 16767
elements in grown defect list: 0

error counter log:

	errors corrected by	total errors	correction algorithm	gigabytes processed	total uncorrected errors	
	ecc	rereads/rewrites		[10 ⁹ bytes]		
read:	0	242	242	356	2842925.933	0
write:	0	176128	176128	441693	171640.872	0
verify:	0	24	24	24	237168.773	0

non-medium error count: 26

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	64	3	-	[- - -]
# 2	background long	completed	64	3	-	[- - -]
# 3	background short	completed	64	1	-	[- - -]

long (extended) self-test duration: 3964 seconds [66.1 minutes]