



Model: SEAGATE ST9600204SS
S/N: 6WN0VE12



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST9600204SS**

Serial: **6WN0VE12**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/22 11:51:02**

End time: **2025/02/22 16:47:39**

Duration: **04:56:37**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **101 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9600204SS
S/N: 6WN0VE12



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9600204SS
revision: FM0A
compliance: SPC-3
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5003b143b57
serial number: 6WN0VE12
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 16:47:40 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 35639:17
manufactured in week 23 of year 2011
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 15
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 15
elements in grown defect list: 4

vendor (seagate cache) information

blocks sent to initiator = 1053004681
blocks received from initiator = 4288275596
blocks read from cache and sent to initiator = 2926095262
number of read and write commands whose size <= segment size = 3569713101
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 35639.28
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	1646709012	109	0	1646709121	1162487.730	0
write:	0	0	6795	6798	329687.342	2
verify:	2778339371	48	0	2778339419	387121.558	0

non-medium error count: 21579

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err [sk asc asq]
# 1	background long	completed	16	7	- [- - -]
# 2	background long	completed	16	3	- [- - -]
# 3	background short	completed	16	1	- [- - -]

long (extended) self-test duration: 6176 seconds [102.9 minutes]



Model: SEAGATE ST9600204SS
S/N: 6WN0VE12

Disk Erasure Report

Page 3 - Smart Data

