



Model: Pliant LB206M

S/N: 41147764

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **Pliant LB206M**

Serial: **41147764**

Size(Apparent): **200 GB, 200049647616 bytes**

Bus: **SAS-SSD**

Size(Real): **200 GB, 200049647616 bytes**

Disk Erasure Details

Start time: **2025/02/22 17:14:10**

End time: **2025/02/22 17:58:53**

Duration: **00:44:43**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **200049647616, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **223 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: Pliant LB206M

S/N: 41147764



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: Pliant
product: LB206M
revision: D323
compliance: SPC-4
user capacity: 200,049,647,616 bytes [200 GB]
logical block size: 512 bytes
lu is resource provisioned, lbprz=1
rotation rate: Solid State Device
form factor: 2.5 inches
logical unit id: 0x5001e8200273dd74
serial number: 41147764
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Feb 22 17:58:57 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

percentage used endurance indicator: 0%
current drive temperature: 41 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 92988:35

manufactured in week 09 of year 2014

specified cycle count over device lifetime: 0

accumulated start-stop cycles: 19

error counter log:

	errors corrected by		total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
	ecc	rereads/ rewrites				
	fast	delayed				
read:	0	0	0	0	8325.209	0
write:	0	0	0	0	56802.279	0

non-medium error count: 18

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	64	2	-	[- - -]
# 2	background long	completed	64	2	-	[- - -]
# 3	background short	completed	64	2	-	[- - -]

long (extended) self-test duration: 1800 seconds [30.0 minutes]