



Model: SEAGATE ST91000640SS  
S/N: 9XG53CS6



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST91000640SS**

Serial: **9XG53CS6**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

## Disk Erasure Details

Start time: **2025/02/22 11:40:09**

End time: **2025/02/22 19:01:05**

Duration: **07:20:56**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/0**

Throughput: **75 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST91000640SS

S/N: 9XG53CS6

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST91000640SS  
revision: AS08  
compliance: SPC-4  
user capacity: 1,000,204,886,016 bytes [1.00 TB]  
logical block size: 512 bytes  
rotation rate: 7200 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c50056f48207  
serial number: 9XG53CS6  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sat Feb 22 19:01:07 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: HARDWARE IMPENDING FAILURE GENERAL HARD DRIVE FAILURE [asc=5d, ascq=10]

current drive temperature: 33 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 19540:49  
manufactured in week 29 of year 2013  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 65  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 166402  
elements in grown defect list: 4099

vendor (seagate cache) information

blocks sent to initiator = 2040515741  
blocks received from initiator = 3248935036  
blocks read from cache and sent to initiator = 2846406298  
number of read and write commands whose size <= segment size = 157668249  
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 19540.82  
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by ecc	fast   delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 <sup>9</sup> bytes]	total uncorrected errors
read:	708100477	559	0	708101036	562	79580.837	9
write:	0	0	0	0	0	19365.278	0
verify:	3424214	23408	0	3447622	24790	69975.286	1241

non-medium error count: 8633

no self-tests have been logged