



Model: SEAGATE ST373455SS

S/N: 3LQ2B2QR

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST373455SS**

Serial: **3LQ2B2QR**

Size(Apparent): **73 GB, 73407820800 bytes**

Bus: **SAS**

Size(Real): **73 GB, 73407820800 bytes**

Disk Erasure Details

Start time: **2025/02/23 06:21:55**

End time: **2025/02/23 07:01:07**

Duration: **00:39:12**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **73407820800, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/174592**

Throughput: **93 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST373455SS

S/N: 3LQ2B2QR

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST373455SS
revision: S527
compliance: SPC-3
user capacity: 73,407,820,800 bytes [73.4 GB]
logical block size: 512 bytes
rotation rate: 15015 rpm
logical unit id: 0x5000c500079b1cdf
serial number: 3LQ2B2QR
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 23 07:01:09 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 32 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 47002:45
elements in grown defect list: 8

vendor (seagate cache) information

blocks sent to initiator = 4092760016
blocks received from initiator = 838754530
blocks read from cache and sent to initiator = 3858175484
number of read and write commands whose size <= segment size = 2045405354
number of read and write commands whose size > segment size = 26148092

vendor (seagate/hitachi) factory information

number of hours powered up = 47002.75
number of minutes until next internal smart test = 20

error counter log:

	errors corrected by		total	correction	gigabytes	total	
	ecc	rereads/	errors	algorithm	processed	uncorrected	
	fast delayed	rewrites	corrected	invocations	[10^9 bytes]	errors	
read:	255920645	52	0	255920697	255920697	111798.738	0
write:	0	0	0	0	0	277576.592	0
verify:	52451417	5	0	52451422	52451422	54574.537	0

non-medium error count: 34

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	-	10	-	[- - -]
# 2	background short	completed	-	9	-	[- - -]

long (extended) self-test duration: 801 seconds [13.3 minutes]