



Model: FUJITSU MBA3147RC

S/N: BJA3P8B09BTC

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **FUJITSU MBA3147RC**

Serial: **BJA3P8B09BTC**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/23 06:22:26**

End time: **2025/02/23 07:41:21**

Duration: **01:18:55**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **93 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: FUJITSU MBA3147RC

S/N: BJA3P8B09BTC

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: FUJITSU
product: MBA3147RC
revision: D306
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
logical unit id: 0x5000000e01e2fbaf0
serial number: BJA3P8B09BTC
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 23 07:41:23 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 34 C
drive trip temperature: 65 C

accumulated power on time, hours:minutes 90644:32
manufactured in week 46 of year 2008
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 30
elements in grown defect list: 0

error counter log:

	errors corrected by		rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
	ecc	fast delayed					
read:	0	17341	17341	17341	20415	511164.693	0
write:	0	40852	40852	40852	51891	127039.060	0
verify:	0	4637	4637	4637	5833	78988.451	0

non-medium error count: 24

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background long	completed	-	0	-	[- - -]
# 2	background short	completed	-	0	-	[- - -]

long (extended) self-test duration: 1456 seconds [24.3 minutes]