



Model: HITACHI HUS153014VLS300

S/N: J4V8A0GC

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HITACHI HUS153014VLS300**

Serial: **J4V8A0GC**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/23 06:22:11**

End time: **2025/02/23 07:45:05**

Duration: **01:22:54**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/49488**

Throughput: **88 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HITACHI HUS153014VLS300

S/N: J4V8A0GC

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HITACHI
product: HUS153014VLS300
revision: A280
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
logical unit id: 0x5000cca0050f2240
serial number: J4V8A0GC
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 23 07:45:07 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C
drive trip temperature: 85 C

accumulated power on time, hours:minutes 30411:25
manufactured in week 41 of year 2007
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 29
elements in grown defect list: 0

vendor (seagate cache) information
blocks sent to initiator = 15234456331747328

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	0	478250	0	478250	1176103	20371.556	0
write:	0	6748560	0	6748560	6832378	36623.353	0
verify:	0	101420	0	101420	104733	73556.151	0

non-medium error count: 0

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	-	0	-	[- - -]
# 2	background short	completed	-	0	-	[- - -]

long (extended) self-test duration: 6422 seconds [107.0 minutes]