



Model: MAXTOR ATLAS10K5_147SAS

S/N: J498E71K

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **MAXTOR ATLAS10K5_147SAS**

Serial: **J498E71K**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2025/02/23 06:22:23**

End time: **2025/02/23 08:15:57**

Duration: **01:53:34**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **64 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: MAXTOR ATLAS10K5_147SAS

S/N: J498E71K

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: MAXTOR
product: ATLAS10K5_147SAS
revision: BP00
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 10002 rpm
logical unit id: 0x50010b900016c2e8
serial number: J498E71K
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 23 08:15:58 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

grown defects during certification = 0
total blocks reassigned during format = 0
total new blocks reassigned = 0
power on minutes since format = 7304280
current drive temperature: 36 C
drive trip temperature: 0 C

accumulated power on time, hours:minutes 121738:02
accumulated start-stop cycles: 34
elements in grown defect list: 0

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	335860071	5467	0	0	0	308452.163	0
write:	0	21	0	0	0	169049.776	0

non-medium error count: 41

last n error events log page

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
			number	(hours)		
# 1	background long	completed	-	1	-	[- - -]
# 2	background short	completed	-	0	-	[- - -]

long (extended) self-test duration: 2880 seconds [48.0 minutes]