



Model: SEAGATE ST600MM0006

S/N: S0M3DYP9

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST600MM0006**

Serial: **S0M3DYP9**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/23 06:21:56**

End time: **2025/02/23 09:37:28**

Duration: **03:15:32**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **153 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0006

S/N: S0M3DYP9

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST600MM0006
revision: LS0C
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5007765a86b
serial number: S0M3DYP9
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 23 09:37:29 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 19880:08
manufactured in week 33 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 182
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 1907
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 3654626257
blocks received from initiator = 3320007168
blocks read from cache and sent to initiator = 2039251710
number of read and write commands whose size <= segment size = 340972839
number of read and write commands whose size > segment size = 17416

vendor (seagate/hitachi) factory information

number of hours powered up = 19880.13
number of minutes until next internal smart test = 53


error counter log:

	errors corrected by		total	correction	gigabytes	total
	ecc	rereads/	errors	algorithm	processed	uncorrected
	fast delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	1938089727	0	0	1938089727	0	67974.360
write:	0	0	33	33	79833.229	0
verify:	816628872	0	0	816628872	0	38655.356

non-medium error count: 98

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	64	705	- [- - -]	
# 2	background short	completed	64	696	- [- - -]	
# 3	background short	completed	64	3	- [- - -]	
# 4	reserved(7)	completed	48	3	- [- - -]	



Model: SEAGATE ST600MM0006
S/N: S0M3DYP9

Disk Erasure Report

Page 3 - Smart Data



5 background short completed 64 1 - [- - -]
long (extended) self-test duration: 3777 seconds [63.0 minutes]