

Model: HGST HUC101860CSS204

S/N: 0BGDNE2F

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **HGST HUC101860CSS204**

Serial: **0BGDNE2F**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/23 06:23:42**

End time: **2025/02/23 10:05:30**

Duration: **03:41:48**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **135 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: HGST HUC101860CSS204

S/N: 0BGDNE2F

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HGST
product: HUC101860CSS204
revision: FJ23
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000cca07d170474
serial number: 0BGDNE2F
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 23 10:05:31 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 38 C
drive trip temperature: 50 C

accumulated power on time, hours:minutes 1560:28
manufactured in week 51 of year 2016
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 8
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 2520
elements in grown defect list: 0

vendor (seagate cache) information
blocks sent to initiator = 99709117123264512

error counter log:

	errors corrected by		total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors	
	fast	delayed					
read:	0	3723132	0	5309832	243870543	223219.096	3419
write:	0	0	0	0	8303517	136777.129	0
verify:	0	779091	0	1310423	30862492	27684.714	39

non-medium error count: 15

no self-tests have been logged