



Model: SEAGATE ST9500620SS
S/N: 9XF33DL3



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST9500620SS**

Serial: **9XF33DL3**

Size(Apparent): **500 GB, 500107862016 bytes**

Bus: **SAS**

Size(Real): **500 GB, 500107862016 bytes**

Disk Erasure Details

Start time: **2025/02/23 06:29:22**

End time: **2025/02/23 11:41:13**

Duration: **05:11:51**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **500107862016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **80 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9500620SS
S/N: 9XF33DL3



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9500620SS
revision: AS0D
compliance: SPC-4
user capacity: 500,107,862,016 bytes [500 GB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 2.5 inches
logical unit id: 0x5000c50058f0de0b
serial number: 9XF33DL3
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 23 11:41:14 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 45385:39
manufactured in week 25 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 133
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 2285
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 4279327652
blocks received from initiator = 4276184133
blocks read from cache and sent to initiator = 198877325
number of read and write commands whose size <= segment size = 373097275
number of read and write commands whose size > segment size = 215

vendor (seagate/hitachi) factory information

number of hours powered up = 45385.65
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	562862141	0	0	562862141	1	5606.050	1
write:	0	0	1	1	1	19829.999	0
verify:	1490253038	0	0	1490253038	0	134294.502	0

non-medium error count: 72

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background long	completed	32	127	- [- - -]	
# 2	background short	completed	32	125	- [- - -]	
# 3	background long	completed	32	46	- [- - -]	
# 4	background short	completed	32	44	- [- - -]	
# 5	background long	completed	32	8	- [- - -]	



Model: SEAGATE ST9500620SS
S/N: 9XF33DL3

Disk Erasure Report

Page 3 - Smart Data



# 6	background long	completed	32	3	- [- - -]
# 7	background short	completed	32	1	- [- - -]

long (extended) self-test duration: 6099 seconds [101.7 minutes]