



Model: HGST HUC101812CSS204 S/N: 0EGZMGND

## Disk Erasure Report

Page 1 - Erasure Status



### Organisation Performing The Disk Erasure

Business Name: Not Applicable (BN)
Business Address: Not Applicable (BA)

Contact Name: Not Applicable (BCN) Contact Phone: Not Applicable (BCP)

#### **Customer Details**

Name: Not Applicable (CN)
Address: Not Applicable (CA)

Contact Name: Not Applicable (CCN)

Contact Phone: Not Applicable (CP)

#### **Disk Information**

Make/Model: HGST HUC101812CSS204 Serial: 0EGZMGND

Size(Apparent): 1200 GB, 1200243695616 bytes Bus: SAS

Size(Real): 1200 GB, 1200243695616 bytes

#### **Disk Erasure Details**

Start time: 2025/02/23 06:29:06 End time: 2025/02/23 13:18:48

Duration: 06:49:42 Status: **ERASED** See Warning!

Method: PRNG Stream PRNG algorithm: XORshiro256

Final Pass(Zeros/Ones/None): Zeros Verify Pass(Last/All/None): Verify Last

\*Bytes Erased: 1200243695616, (100.00%) Rounds(completed/requested): 1/1

HPA/DCO: Unknown HPA/DCO Size: Unknown

Errors(pass/sync/verify): 0/0/0 Throughput: 146 MB/sec

Information: Warning HPA/DCO data unavailable, can not determine hidden sector status.

Technician/Operator ID Signature:

Name/ID: Not Applicable (OTN)

<sup>\*</sup> bytes erased: The amount of drive that's been erased at least once





### Model: HGST HUC101812CSS204 S/N: 0EGZMGND

# Disk Erasure Report





smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build) copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HGST

HUC101812CSS204 product:

revision: FJ45 compliance: SPC-4

user capacity: 1,200,243,695,616 bytes [1.20 TB]

logical block size: 512 bytes formatted with type 2 protection

8 bytes of protection information per logical block

lu is fully provisioned

10000 rpm rotation rate: form factor: 2.5 inches

logical unit id: 0x5000cca08037b0ec serial number: 0EGZMGND device type: disk

transport protocol: SAS (SPL-3) local time is: Sun Feb 23 13:18:59 2025 GMT local time is:

smart support is: Available - device has SMART capability. smart support is: Enabled

temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 45 C drive trip temperature: 50 C

accumulated power on time, hours:minutes 50976:50

manufactured in week 51 of year 2016

specified cycle count over device lifetime: 50000

accumulated start-stop cycles: 74

specified load-unload count over device lifetime: 600000

accumulated load-unload cycles: 2176 elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 35127668957511680

error counter log:

	_						
	errors	corrected	by	total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10 <sup>9</sup> bytes]	errors
read:	0	9	0	30	49858447	110505.007	0
write:	0	0	0	0	347682	135507.268	0
verify:	0	351	0	677	203823	5760.065	0

non-medium error count:

smart self-test log

num	test	status	segment	lifetime	lba_first_err [sk asc asq]
	description		number	(hours)	
# 1	background short	completed	80	47	- []
# 2	background short	completed	80	9	- []
# 3	reserved(7)	completed	64	9	- []
# 4	background short	completed	80	3	- []
# 5	reserved(7)	completed	64	3	- []

long (extended) self-test duration: 8851 seconds [147.5 minutes]