

Model: SEAGATE ST1200MM0088

S/N: S40197WP

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST1200MM0088**

Serial: **S40197WP**

Size(Apparent): **1200 GB, 1200243695616 bytes**

Bus: **SAS**

Size(Real): **1200 GB, 1200243695616 bytes**

## Disk Erasure Details

Start time: **2025/02/23 06:29:32**

End time: **2025/02/23 13:58:21**

Duration: **07:28:49**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **1200243695616, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **133 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST1200MM0088

S/N: S40197WP

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST1200MM0088  
revision: TT31  
compliance: SPC-4  
user capacity: 1,200,243,695,616 bytes [1.20 TB]  
logical block size: 512 bytes  
formatted with type 2 protection  
8 bytes of protection information per logical block  
lu is fully provisioned  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c50096728013  
serial number: S40197WP  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sun Feb 23 13:58:30 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>  
total blocks reassigned during format <not available>  
total new blocks reassigned = 0  
power on minutes since format <not available>  
current drive temperature: 32 C  
drive trip temperature: 60 C

accumulated power on time, hours:minutes 54015:07  
manufactured in week 06 of year 2016  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 65  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 2983  
elements in grown defect list: 0


vendor (seagate cache) information  
blocks to initiator = 1591967477  
blocks received from initiator = 694456880  
blocks read from cache and sent to initiator = 2005168188  
number of read and write commands whose size <= segment size = 732854426  
number of read and write commands whose size > segment size = 10

vendor (seagate/hitachi) factory information  
number of hours powered up = 54015.12  
number of minutes until next internal smart test = 47

error counter log:		errors corrected by		total	correction	gigabytes	total
	ecc	fast   delayed	rereads/ rewrites	errors corrected	algorithm invocations	processed [10^9 bytes]	uncorrected errors
read:	2168972536	3	0	2168972539	3	620148.848	0
write:	0	0	56	56	56	134433.292	0
verify:	893748492	3	0	893748495	3	390168.089	0

non-medium error count: 1

smart self-test log



Model: SEAGATE ST1200MM0088  
S/N: S40197WP



# Disk Erasure Report

Page 3 - Smart Data

---

num	test	status	segment	lifetime	lba_first_err	[sk	asc	asq]
	description		number	(hours)				
# 1	background short	completed	80	3	-	[-	-	-]
# 2	reserved(7)	completed	64	3	-	[-	-	-]

long (extended) self-test duration: 7630 seconds [127.2 minutes]