



Model: SEAGATE ST1200MM0088

S/N: S40144W2

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST1200MM0088**

Serial: **S40144W2**

Size(Apparent): **1200 GB, 1200243695616 bytes**

Bus: **SAS**

Size(Real): **1200 GB, 1200243695616 bytes**

## Disk Erasure Details

Start time: **2025/02/23 06:29:32**

End time: **2025/02/23 13:59:22**

Duration: **07:29:50**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **1200243695616, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **133 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST1200MM0088

S/N: S40144W2

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST1200MM0088  
revision: TT31  
compliance: SPC-4  
user capacity: 1,200,243,695,616 bytes [1.20 TB]  
logical block size: 512 bytes  
formatted with type 2 protection  
8 bytes of protection information per logical block  
lu is fully provisioned  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c50096018e33  
serial number: S40144W2  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sun Feb 23 13:59:33 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>  
total blocks reassigned during format <not available>  
total new blocks reassigned = 0  
power on minutes since format <not available>  
current drive temperature: 33 C  
drive trip temperature: 60 C

accumulated power on time, hours:minutes 54014:44  
manufactured in week 07 of year 2016  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 67  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 2882  
elements in grown defect list: 0


vendor (seagate cache) information  
blocks sent to initiator = 1147266  
blocks received from initiator = 847829112  
blocks read from cache and sent to initiator = 4256791755  
number of read and write commands whose size <= segment size = 662786047  
number of read and write commands whose size > segment size = 42

vendor (seagate/hitachi) factory information  
number of hours powered up = 54014.73  
number of minutes until next internal smart test = 46

error counter log:							
	errors corrected by		total	correction	gigabytes	total	
	ecc	rereads/	errors	algorithm	processed	uncorrected	
	fast   delayed	rewrites	corrected	invocations	[10^9 bytes]	errors	
read:	315323881	1	0	315323882	1	570192.366	0
write:	0	0	95	95	132278.832	0	0
verify:	838103125	2	0	838103127	2	390162.919	0

non-medium error count: 2

smart self-test log



Model: SEAGATE ST1200MM0088  
S/N: S40144W2



# Disk Erasure Report

Page 3 - Smart Data

---

num	test	status	segment	lifetime	lba_first_err	[sk	asc	asq]
	description		number	(hours)				
# 1	background short	completed	80	3	-	[-	-	-]
# 2	reserved(7)	completed	64	3	-	[-	-	-]

long (extended) self-test duration: 7630 seconds [127.2 minutes]