




#### Model: SEAGATE ST300MP0026 S/N: WAE0G6BA

## Disk Erasure Report





	C	rganisation	Performing	The	Disk	<b>Erasure</b>
--	---	-------------	------------	-----	------	----------------

Business Name: GridJet

**Business Address:** 

Contact Name: **GDW-LDS-6** Contact Phone:

**Customer Details** 

Name: Gridjet

Address:

Contact Name: Contact Phone:

**Disk Information** 

Make/Model: SEAGATE ST300MP0026 Serial: WAE0G6BA

Size(Apparent): 300 GB, 30000000000 bytes Bus: SAS

Size(Real): 300 GB, 30000000000 bytes

**Disk Erasure Details** 

Start time: 2025/02/23 13:04:41 End time: 2025/02/23 14:22:05

Duration: 01:17:24 Status: **ERASED** See Warning!

Method: PRNG Stream PRNG algorithm: XORshiro256

Final Pass(Zeros/Ones/None): Zeros Verify Pass(Last/All/None): Verify Last

\*Bytes Erased: 30000000000, (100.00%) Rounds(completed/requested): 1/1

HPA/DCO: Unknown HPA/DCO Size: Unknown

Errors(pass/sync/verify): 0/0/0 Throughput: 193 MB/sec

Information: Warning HPA/DCO data unavailable, can not determine hidden sector status.

Technician/Operator ID Signature:

Name/ID: Auto Wipe

<sup>\*</sup> bytes erased: The amount of drive that's been erased at least once





#### Model: SEAGATE ST300MP0026 S/N: WAE0G6BA

### Disk Erasure Report





```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
=== start of information section ===
vendor:
                      SEAGATE
product:
                      ST300MP0026
revision:
                      KT3A
compliance:
                      SPC-4
user capacity:
                      300,000,000,000 bytes [300 GB]
logical block size:
                      512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
lu is fully provisioned
                   15000 rpm
2.5 inches
rotation rate:
form factor:
logical unit id: 0x5000c500b753f4e3
serial number: WAE0G6BA
device type: disk
device type:
                     disk
transport protocol: SAS (SPL-3) local time is: Sun Feb 23 14:22:06 2025 GMT
local time is:
smart support is: Available - device has SMART capability. smart support is: Enabled
temperature warning: Disabled or Not Supported
=== start of read smart data section ===
smart health status: OK
grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned = 0
power on minutes since format <not available>
current drive temperature: 39 C drive trip temperature: 60 C
drive trip temperature:
accumulated power on time, hours:minutes 26150:01
manufactured in week 03 of year 2018
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 30
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 1114
elements in grown defect list: 0
vendor (seagate cache) information
 blocks sent to initiator = 465579736
  blocks received from initiator = 3676664995
  blocks read from cache and sent to initiator = 1490516788
  number of read and write commands whose size <= segment size = 376874036
 number of read and write commands whose size > segment size = 207
vendor (seagate/hitachi) factory information
 number of hours powered up = 26150.02
 number of minutes until next internal smart test = 49
error counter log:
                                                                gigabytes
           errors corrected by
                                         total correction
           ecc rereads/ errors algorithm fast | delayed rewrites corrected invocations
                                                                  processed uncorrected
                                                                [10^9 bytes] errors
       159855.414
read:
                                                             57837.127
write:
                                    0 2288932833
verify: 2288932833
                          0
                                                            0
                                                                   48091.306
                                                                                         0
non-medium error count:
                              151
smart self-test log
```





Model: SEAGATE ST300MP0026 S/N: WAE0G6BA

# Disk Erasure Report





num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk	asc	asq]
	reserved(7) background short		64 96	3 1				- ] - ]

long (extended) self-test duration: 1800 seconds [30.0 minutes]