



Model: SEAGATE ST600MP0006

S/N: WAF1GM3Y0000E940GUQ5

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **SEAGATE ST600MP0006**

Serial: **WAF1GM3Y0000E940GUQ5**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/23 13:03:55**

End time: **2025/02/23 16:09:44**

Duration: **03:05:49**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **161 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST600MP0006

S/N: WAF1GM3Y0000E940GUQ5

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST600MP0006
revision: N003
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 15052 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500c174f18f
serial number: WAF1GM3Y0000E940GUQ5
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sun Feb 23 16:10:07 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned <not available>
power on minutes since format <not available>
current drive temperature: 40 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 34930:46
manufactured in week 16 of year 2019
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 16
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 1461
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1172339089
blocks received from initiator = 2344247136
blocks read from cache and sent to initiator = 12728
number of read and write commands whose size <= segment size = 3767
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information

number of hours powered up = 34930.77
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by	total	correction	gigabytes	total
	ecc	errors	algorithm	processed	uncorrected
	fast delayed	rereads/ rewrites	corrected invocations	[10^9 bytes]	errors
read:	1172340304	0	0	600.238	0
write:	0	0	0	1200.274	0

non-medium error count: 0

[gltsd (global logging target save disable) set. enable save with '-s on']
no self-tests have been logged



Model: SEAGATE ST600MP0006

S/N: WAF1GM3Y0000E940GUQ5

Disk Erasure Report

Page 3 - Smart Data

