



Model: SEAGATE ST1000NX0453

S/N: W4723K7H0000E905E1JN

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST1000NX0453**

Serial: **W4723K7H0000E905E1JN**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/02/24 15:08:31**

End time: **2025/02/24 23:37:39**

Duration: **08:29:08**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **98 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST1000NX0453

S/N: W4723K7H0000E905E1JN

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST1000NX0453
revision: N005
compliance: SPC-4
user capacity: 1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 7200 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500bba7102f
serial number: W4723K7H0000E905E1JN
device type: disk
transport protocol: SAS (SPL-3)
local time is: Mon Feb 24 23:37:41 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned <not available>
power on minutes since format <not available>
current drive temperature: 31 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 13527:11
manufactured in week 34 of year 2018
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 8
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 570
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1957353594
blocks received from initiator = 3907051741
blocks read from cache and sent to initiator = 382194
number of read and write commands whose size <= segment size = 15205
number of read and write commands whose size > segment size = 1103

vendor (seagate/hitachi) factory information

number of hours powered up = 13527.18
number of minutes until next internal smart test = 0

error counter log:

	errors corrected by ecc	fast delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	3320714566	0	0	3320714566	0	1000.486	0
write:	0	0	0	0	0	2000.415	0
verify:	5348829	0	0	5348829	0	1.679	0

non-medium error count: 0

[gltsd (global logging target save disable) set. enable save with '-s on']
no self-tests have been logged



Model: SEAGATE ST1000NX0453
S/N: W4723K7H0000E905E1JN

Disk Erasure Report

Page 3 - Smart Data

